

Outperform every day.

Project:

Item Number:

Quantity:

CAYENNE®LIGHT STRIPS



Cavenne® Light Strip with Standard 40 Watt Bulbs

DESCRIPTION

The Cayenne® Light Strips illuminate food serving display areas or food preparation areas.

FEATURES

- Structurally engineered aluminum housing offers maximum strength with minimal weight.
- Standard light reflector directs maximum light to the display
- Includes shatterproof bulbs available in either 40 watt standard or 60 watt display styles.
- 120V, single-phase.
- Includes onboard toggle switch controls located on the operator's left.
- 6" (15.2 cm) pigtail leads located on the server's left.
- Recessed dovetail channel allows for installation of Kool-Touch® decorative trim.
- Optional Kool-Touch® thermoplastic black trim. See back page for details.
- Replacement bulbs available. See back page for details.
- Includes chain mounting tabs and a set of 1" (2.5 cm) top mounting brackets.
- One-year parts and labor warranty.

Note: All light strips are custom ordered and therefore cannot be cancelled or returned per Vollrath Terms & Conditions.

Agency Listings





MODELS

	40 Watt Sta	ndard Bulbs	40 Watt Standard Bulbs with Extra Bulbs			
Length	Model No.	Total No. lodel No. of bulbs		Total No. of bulbs		
18" (47.7 cm)	7286000	2	n/a	n/a		
24" (60.9 cm)	7286100	2	n/a	n/a		
30" (76.2 cm)	7286200	2	7286201	4		
36" (91.4 cm)	7286300	4	7286301	6		
42" (106.6 cm)	7286400	4	7286401	6		
48" (121.9 cm)	7286500	4	7286501	8		
54" (137.1 cm)	7286600	6	7286601	8		
60" (152.4 cm)	7286700	6	7286701	10		
66" (167.6 cm)	7286800	6	7286801	10		
72" (182.8 cm)	7286900	10				
(102.0 0111)	720000	6	7286901	10		
72 (102.0 011)	60 Watt Dis			splay Bulbs		
Length			60 Watt Dis	splay Bulbs		
	60 Watt Dis	splay Bulbs Total No.	60 Watt Dis with Ext	splay Bulbs ra Bulbs Total No.		
Length	60 Watt Dis	splay Bulbs Total No. of bulbs	60 Watt Dis with Ext Model No.	splay Bulbs ra Bulbs Total No. of bulbs		
Length 18" (47.7 cm)	60 Watt Dis Model No. 7286002	splay Bulbs Total No. of bulbs	60 Watt Diswith Ext Model No. n/a	ra Bulbs rotal No. of bulbs		
Length 18" (47.7 cm) 24" (60.9 cm)	60 Watt Dis Model No. 7286002 7286102	Total No. of bulbs 2 2	60 Watt Diswith Ext Model No. n/a n/a	splay Bulbs ra Bulbs Total No. of bulbs n/a n/a		
Length 18" (47.7 cm) 24" (60.9 cm) 30" (76.2 cm)	60 Watt Dis Model No. 7286002 7286102 7286202	Total No. of bulbs 2 2 2	60 Watt Diswith Ext Model No. n/a n/a 7286203	ra Bulbs ra Bulbs Total No. of bulbs n/a n/a 4		
Length 18" (47.7 cm) 24" (60.9 cm) 30" (76.2 cm) 36" (91.4 cm)	60 Watt Dis Model No. 7286002 7286102 7286202 7286302	Total No. of bulbs 2 2 2 4	60 Watt Diswith Ext Model No. n/a n/a 7286203 7286303	ra Bulbs ra Bulbs Total No. of bulbs n/a n/a 4 6		
Length 18" (47.7 cm) 24" (60.9 cm) 30" (76.2 cm) 36" (91.4 cm) 42" (106.6 cm)	60 Watt Dis Model No. 7286002 7286102 7286202 7286302 7286402	Total No. of bulbs 2 2 2 4 4	60 Watt Diswith Ext Model No. n/a n/a 7286203 7286303 7286403	ra Bulbs ra Bulbs Total No. of bulbs n/a n/a 4 6 6		
Length 18" (47.7 cm) 24" (60.9 cm) 30" (76.2 cm) 36" (91.4 cm) 42" (106.6 cm) 48" (121.9 cm)	60 Watt Dis Model No. 7286002 7286102 7286202 7286302 7286402 7286502	Total No. of bulbs 2 2 2 4 4 4	60 Watt Diswith Ext Model No. n/a n/a 7286203 7286303 7286403 7286503	ra Bulbs ra Bulbs Total No. of bulbs n/a n/a 4 6 6 8		
Length 18" (47.7 cm) 24" (60.9 cm) 30" (76.2 cm) 36" (91.4 cm) 42" (106.6 cm) 48" (121.9 cm) 54" (137.1 cm)	60 Watt Dis Model No. 7286002 7286102 7286202 7286302 7286402 7286502 7286602	Total No. of bulbs 2 2 2 4 4 4 6	60 Watt Diswith Ext Model No. n/a n/a 7286203 7286303 7286403 7286503 7286603	ra Bulbs ra Bulbs Total No. of bulbs n/a n/a 4 6 6 8 8		

Due to continued product improvement, please consult www.vollrath.com for current product specifications.

UL CLEARANCE REQUIREMENTS

One inch (2.5 cm) clearance required around all sides of the light strip.

WARRANTY: All models shown come with Vollrath's standard warranty against defects in materials and workmanship. For full warranty details, please refer to the Vollrath Equipment and Smallwares Catalog.

Approvals	Date			



www.vollrath.com

CAYENNE®LIGHT STRIPS

Units are supplied with chain mounting tabs and a set of 1" (2.5 cm) top surface mounting brackets.



Item No.	Description	Case Lot
44545	Top Surface Mount Bracket – 1" (2.5 cm)	2
44546	Top Surface Mount Bracket – 2" (5.1 cm)	2
44140	Center Mount Bracket – 1" (2.5 cm)	1
44145	Center Mount Bracket – 2" (5.1 cm)	1

Recommended Number of Center Mount Brackets

Length	Recommended Brackets
18" (45.7)	2
24" (60.9)	2
30" (76.2)	2
36" (91.4)	2
42" (106.6)	3
48" (121.9)	3
54" (137.1)	3
60" (152.4)	3
66" (167.6)	3
72" (182.8)	3

ACCESSORIES

☐ Kool-Touch® Trim



Item No.	Description
17897xx	Enter unit length at end of part number to add this accessory. One set includes operator and server
	side coverage. Field trimming required.


☐ Replacement Bulbs



Item No.	Description	Case Lot ^þ
	40W Teflon® coated, shatterproof bulbs	4
23026	60W Satin Spun, shatterproof bulbs	4

DIMENSIONS AND SPECIFICATIONS

All dimensions are in inches (cm). All weights are in Lbs. (kg).



		Amp Draw							
		With Standard No. Bulbs		With Extra Bulbs		Dimensions			
Length	Base Item No.	40W	60W	40W	60W	Length (A)	Height (B)	Width (C)	Shipping Weights
18" (47.7)	72860	0.7	1	n/a	n/a	18" (47.7)		3" (7.6) All Units	4.0 (1.8)
24" (60.9)	72861	0.7	1	n/a	n/a	24" (60.9)			4.9 (2.2)
30" (76.2)	72862	0.7	1	1.4	2	30" (76.2)			5.9 (2.6)
36" (91.4)	72863	1.4	2	2	3	36" (91.4)	2.88" (7.32) All Units		6.8 (3.0)
42" (106.6)	72864	1.4	2	2	3	42" (106.6)			7.6 (3.4)
48" (121.9)	72865	1.4	2	2.7	4	48" (121.9)			8.5 (3.8)
54" (137.1)	72866	2.1	3	2.7	4	54" (137.1)			9.3 (4.2)
60" (152.4)	72867	2.1	3	3.4	5	60" (152.4)			10.2 (4.6)
66" (167.6)	72868	2.1	3	3.4	5	66" (167.6)			11.0 (5.0)
72" (182.8)	72869	2.1	3	3.4	5	72" (182.8)			12.5 (5.6)



Outperform every day.

The Vollrath Company, L.L.C. 1236 North 18th Street Sheboygan, WI 53081-3201 U.S.A.

Customer Service: 800.628.0830 Canada Customer Service: 800.695.8560 Main Fax: 800.752.5620 or

Technical Services: 800.628.0832 Technical Services Fax: 920.459.5462